CUSTOM INSULATION

Bespoke Acoustic and Thermal Insulation Specialists



Process

Typically, our process starts by understanding the requirements of our customer, so we can establish an appropriate quality product for their needs. The insulation comes in multiple forms, in various densities and colours, made especially with different markets in mind. It is then converted in-house and shaped to the customer's needs. The product can be faced or wrapped in multiple different options for protection, reflectivity or to prevent water ingress. A selfadhesive backing can be applied to allow easy installation. We achieve the desired design utilising a combination of CNC technology, saws, presses, guillotines and hand finishing. We then collaborate with our customer on the finishing, providing installation aids and bespoke kitting to ensure installation is accurate and easy.

Customisation

Converting the material ourselves, we can supply any thickness you require. Catering to a wide range of shapes and sizes, we utilise a high daylight CNC knife to accurately cut sheets up to 100mm thick alongside press tooling to give fast repeatable processing for any required shape. This gives a made to-measure product that fits around bolts, fixings and intricate shapes.



Custom Insulation has had many years of experience in the insulation industry going all the way back to 1890 under the banner of Hodgson & Hodgson Group. We have provided insulation solutions in specialist industry sectors including construction, transportation, appliances and industrial.







Example material specifications for Industrial.



INSULATION

Superwool Plus/ HT

A binder free blanket produced from pure raw materials. Superwool has excellent thermal properties, good sound absorption, improved handling strength and reduced nuisance particles, resulting in an easy to use blanket with reduced irritation when handling.

Material Data Sheet

0.25

Issue 1 08/2021

| Thermal Conductivity (W/mK) | 64 | 80 | 00 | |
|-----------------------------|------|------|------|------|
| 200°C | | | 96 | 128 |
| 400°C | 0.06 | 0.06 | | |
| 600°C | 0.11 | 0.09 | 0.05 | 0.05 |
| 800°C | 0.18 | 0.15 | 0.09 | 0.08 |
| 1000°C | 0.29 | 0.24 | 0.14 | 0.12 |
| | 0.42 | 0.36 | 0.21 | 0.18 |
| | | 1.00 | 0.29 | 0.05 |

NOTE: Only 96kg/m³ and 128kg/m³ are available for Superwool HT. Thermal conductivity differs slightly - contact Custom Insulation Ltd for further information.



Custom Insulation Ltd Crown Industrial Estate Anglesey Road Burton upon Trent DE14 3PA

01283 500333 www.custominsulation.co.uk enquiries@custominsulation.co.uk

All given figures stand for information according to our own knowledge but should not be used as specification or guaranteed data.

Custom Insulation Ltd

Crown Industrial Estate Anglesey Road Burton upon Trent DE14 3PA

Contact us: 01283 500333 enquiries@custominsulation.co.uk

